



ISO/IEC 19752 Yield Test Report

E450dn High Yield Print Cartridge

Printer: E450dn

Part Numbers: E450H11A E450H11E E450H11L E450H11P
E450H21A E450H21E E450H21L E450H21P

Declaration of **Average Cartridge Yield 11000 standard pages**
Yield: **Declared yield value in accordance with ISO/IEC 19752**

Average 11409
Std Dev 337
90% Lower 11200
Confidence

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

start **stop**
Date tested 20-Jun-2006 26-Jun-2006

Number of cartridges in testing 9
Qty. of cartridges used in calculation 9
Shake Procedure 1st shake At toner low
2nd shake At fade
Print mode Continuous
Number of printers tested 3
Media used Hammermill Tidal - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version E450dn G9
Operating system Window XP
Application software Acrobat version 7.0.0
Test page version 19752_Test_Chart_Ver.200406.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS061531BAD	6203HCF	73	23	75	24	72	22	53	55	46	11,762	Yes
CAS061531BA5	6203HCK	73	23	75	24	72	22	53	55	46	11,191	Yes
CAS061531B96	6203HDT	73	23	75	24	72	22	53	55	46	11,468	Yes
CAS061531B92	6203HCF	73	23	74	24	72	22	55	56	51	11,709	Yes
CAS061531B98	6203HCK	73	23	74	24	72	22	55	56	51	11,560	Yes
CAS061531B9E	6203HDT	73	23	74	24	72	22	55	56	51	11,399	Yes
CAS061531B91	6203HCF	72	22	73	23	71	21	55	57	50	11,370	Yes
CAS061531B9D	6203HCK	72	22	73	23	71	21	55	57	50	11,580	Yes
CAS061531BD3	6203HDT	72	22	73	23	71	21	55	57	50	10,640	Yes
			-18		-18		-18					No
			-18		-18		-18					No
			-18		-18		-18					No

Comments and or exceptions: