



ISO/IEC 19752 Yield Test
Report

T650, T652, T654 High Yield Print Cartridge

Printer: T650

Declaration of **Average Cartridge Yield 25000 standard pages**
Yield: **Declared yield value in accordance with ISO/IEC 19752**

Average 29272
Std Dev 759
90% Lower 28801
Confidence

For questions concerning testing
contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

start
Date tested 8-Aug-2008

stop
12-Aug-2008

Number of cartridges in testing 9
Qty. of cartridges used in calculation 9
Shake Procedure 1st shake At toner low
2nd shake At fade
Print mode Continuous
Number of printers tested 3
Media used Hammermill Tidal DP - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version T65x version 1
Operating system Windows 2000
Application software Acrobat version 7.1.0
Test page version 19752 Test Chart.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS081432258	PLT1007	72	22	73	23	71	21	51	54	48	30,369	Yes
CAS081432239	PLT1007	71	22	73	23	70	21	51	53	48	30,013	Yes
CAS081432249	PLT1007	71	22	72	22	70	21	49	51	47	29,788	Yes
CAS081432227	PLT1012	71	22	73	23	70	21	51	54	49	28,410	Yes
CAS081432253	PLT1012	71	22	72	22	70	21	49	53	47	28,355	Yes
CAS081432255	PLT1012	71	22	72	22	70	21	50	53	48	28,568	Yes
CAS08143225E	PLT1011	71	22	73	23	70	21	51	54	48	29,041	Yes
CAS08143223B	PLT1011	71	22	72	22	70	21	51	53	48	29,897	Yes
CAS081432224	PLT1011	71	22	72	22	70	21	49	51	47	29,004	Yes

Comments and or exceptions: