



ISO/IEC 19752 Yield Test  
Report

T650, T652, T654 Print Cartridge, T650 Ship With  
Printer: T650

Declaration of **Average Cartridge Yield 7000 standard pages**  
Yield: **Declared yield value in accordance with ISO/IEC 19752**

**Average** 8975  
**Std Dev** 323  
**90% Lower** 8775  
**Confidence**

**For questions concerning testing  
contact:**

Lexmark International Inc.  
740 West New Circle Rd.  
Lexington, Ky. 40550 USA  
Attn: Laser Supplies Product Manager

**start**  
**Date tested** 7-Aug-2008

**stop**  
8-Aug-2008

Number of cartridges in testing 9  
Qty. of cartridges used in calculation 9  
Shake Procedure 1st shake At toner low  
2nd shake At fade  
Print mode Continuous  
Number of printers tested 3  
Media used Hammermill Tidal DP - 20# - Letter  
Paper feed orientation Short Edge Feed (SEF)  
Driver version T65x version 1  
Operating system Windows 2000  
Application software Acrobat version 7.1.0  
Test page version 19752 Test Chart.pdf

| Cartridge testing data: |         | Temperature |           |           |           |           |           | Humidity |     |     | Cartridge<br>Yield | Cartridge<br>used in<br>Calculation |
|-------------------------|---------|-------------|-----------|-----------|-----------|-----------|-----------|----------|-----|-----|--------------------|-------------------------------------|
| Cartridge               | Printer | Avg<br>°F   | Avg<br>°C | Max<br>°F | Max<br>°C | Min<br>°F | Min<br>°C | Avg      | Max | Min |                    |                                     |
| CAS0808019D8            | PLT1007 | 71          | 22        | 71        | 22        | 70        | 21        | 55       | 57  | 54  | 9,339              | Yes                                 |
| CAS0808019EC            | PLT1007 | 70          | 21        | 72        | 22        | 69        | 21        | 55       | 57  | 52  | 8,980              | Yes                                 |
| CAS0808019C2            | PLT1007 | 71          | 22        | 72        | 22        | 71        | 21        | 53       | 54  | 52  | 9,259              | Yes                                 |
| CAS0808019E4            | PLT1012 | 71          | 22        | 71        | 22        | 70        | 21        | 55       | 56  | 54  | 8,887              | Yes                                 |
| CAS0808019B1            | PLT1012 | 71          | 21        | 72        | 22        | 69        | 21        | 55       | 57  | 53  | 8,503              | Yes                                 |
| CAS0808019D6            | PLT1012 | 71          | 22        | 72        | 22        | 71        | 21        | 53       | 54  | 52  | 9,272              | Yes                                 |
| CAS0808019ED            | PLT1011 | 71          | 22        | 71        | 22        | 70        | 21        | 55       | 56  | 54  | 9,253              | Yes                                 |
| CAS0808019E7            | PLT1011 | 70          | 21        | 72        | 22        | 69        | 21        | 55       | 57  | 53  | 8,603              | Yes                                 |
| CAS0808019E9            | PLT1011 | 71          | 22        | 72        | 22        | 70        | 21        | 53       | 55  | 52  | 8,678              | Yes                                 |
|                         |         |             |           |           |           |           |           |          |     |     |                    |                                     |
|                         |         |             |           |           |           |           |           |          |     |     |                    |                                     |
|                         |         |             |           |           |           |           |           |          |     |     |                    |                                     |

Comments and or exceptions: