



ISO/IEC 19752 Yield Test Report

X463, X464, X466 Extra High Yield Print Cartridge

Printer: X463

Declaration of **Average Cartridge Yield 15000 standard pages**
Yield: **Declared yield value in accordance with ISO/IEC 19752**

Average 16288
Std Dev 405
90% Lower 16036
Confidence

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 25-Jun-2008 stop 2-Jul-2008

Number of cartridges in testing 9
Qty. of cartridges used in calculation 9
Shake Procedure 1st shake At toner low
2nd shake At fade
Print mode Continuous
Number of printers tested 3
Media used Tidal Hammermill - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version Long Bow Lexmark G9
Operating system Windows XP SP2
Application software Acrobat version 7.0.0
Test page version 19752_Test_Chart_Ver200406.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS081652310	320065	70	21	71	22	69	20	48	52	45	17,039	Yes
CAS081652311	320032	70	21	71	22	69	20	48	52	45	16,530	Yes
CAS0816522BB	320066	70	21	71	22	69	20	48	52	45	15,840	Yes
CAS08165230F	320065	72	22	74	23	69	20	47	54	40	16,729	Yes
CAS08165230C	320032	72	22	74	23	69	20	47	54	40	15,910	Yes
CAS081652312	320066	72	22	74	23	69	20	47	54	40	16,030	Yes
CAS08165230F	320065	72	22	74	23	70	21	48	54	45	16,100	Yes
CAS0816522B3	320032	72	22	74	23	70	21	48	54	45	16,070	Yes
CAS0816522F0	320066	72	22	74	23	70	21	48	54	45	16,340	Yes

Comments and or exceptions: