



ISO/IEC 19752 Yield Test Report

X830e/X832e Print Cartridge

Printer: X832e

Part Numbers: X8302KH

Declaration of **Average Cartridge Yield 30000 standard pages**
Yield: **Declared yield value in accordance with ISO/IEC 19752**

Average 33007
Std Dev 833
90% Lower 32490
Confidence

For questions concerning testing

contact:

Lexmark International Inc.

740 West New Circle Rd.

Lexington, Ky. 40550 USA

Attn: Laser Supplies Product Manager

start **stop**
Date tested 8-Jun-2005 15-Jun-2005

Number of cartridges in testing 9
Qty. of cartridges used in calculation 9
Shake Procedure 1st shake At toner low
2nd shake At toner low
Print mode Continuous
Number of printers tested 3
Media used Boise Cascade X-9 - 20# - Letter
Paper feed orientation Long Edge Feed (LEF)
Driver version W820 Driver Version 7.4.2
Operating system Windows XP SP2
Application software Adobe Acrobat Version 6.0.2
Test page version IS_19752_Testpage.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
J0-40800-5412K30-CT350006	152970	74	23	75	24	73	23	55	60	53	33,290	Yes
J0-41023-5408K30-CT350006	165579	74	23	75	24	73	23	55	60	53	32,840	Yes
J0-41381-5411K30-CT350006	165601	74	23	75	24	73	23	55	60	53	33,640	Yes
J0-41024-5408K30-CT350006	152970	75	24	75	24	74	23	55	60	52	32,560	Yes
J0-41028-5408K30-CT350006	165579	75	24	75	24	74	23	55	60	52	34,180	Yes
J0-41027-5408K30-CT350006	165601	75	24	75	24	74	23	55	60	52	33,000	Yes
J0-40811-5412K30-CT350006	152970	76	24	77	25	74	23	53	60	47	31,320	Yes
J0-41018-5408K30-CT350006	165579	76	24	77	25	74	23	53	60	47	32,570	Yes
J0-41011-5408K30-CT350006	165601	76	24	77	25	74	23	53	60	47	33,660	Yes

Comments and or exceptions: